


# INSTANT ELECTRIC WATER HEATER

## Features

- ↻ Electric central water heater
- ↻ Indoor heating function
- ↻ 220-240 V or 380V(3 phase)
- ↻ Use with electrical energy (single phase or three phase)
- ↻ Temperature of 30-85°C
- ↻ Dry heating protect of 105°C
- ↻ Anti-freezing protect temperature lower than 5°C
- ↻ Over temperature protect of 85°C



All room thermostats  
the possibility to use with



Device Dimensions  
656 x 465 x 320 mm



Frost protection feature

## AREAS OF USE



Housing



Housing  
Estate



Hospital



Plaza

# INSTANT ELECTRIC WATER HEATER

POWER	3KW	4KW	5KW	8KW	9KW	12KW
PHASE	1					
VOLTAGE	220V-240V ,50Hz/60Hz					
CURRENT(A)	13.7-18.2	18.2	22.8	36.4	40.9	54.6
CIRCUIT BREAKER REQUIREMENT(A)	≥20	≥32	≥32	≥40	≥40	≥60
COPPER CORE WIRE REQUIREMENT	2.5m m <sup>2</sup>	2.5m m <sup>2</sup>	2.5m m <sup>2</sup>	2.5m m <sup>2</sup>	2.5m m <sup>2</sup>	2.5m m <sup>2</sup>
TEMP. SETTING ARRANGE	30°C - 55°C					
WATER PRESSURE	0.02-0.6Mpa					
OVERHEAT PROTECTION	60°C					
THERMAL CUT-OFF	90°C					
PIPE SECTION	G 1/2"					
WATERPROOF LEVEL	IPX4					
SAFETY LEVEL	IPX25					

